

# **PRODUCT DATASHEET**SST CLAS A 60 9 W/2700K E27

LED SUPERSTAR CLASSIC A | Dimmable LED lamps, classic bulb shape



# AREAS OF APPLICATION

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

#### **PRODUCT BENEFITS**

- Low energy consumption
- High color consistency thanks to narrow binning
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

#### **PRODUCT FEATURES**

- LED alternative to conventional lamps
- Good quality of light; color rendering index  $R_a$ :  $\geq$  80; constant chromaticity
- High color consistency: < 6 SDCM
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Mercury-free lamps



## **TECHNICAL DATA**

#### Electrical data

Rated wattage	9.00 W
Nominal wattage	9.00 W
Nominal voltage	220240 V
Max. lamp no. on circuit break. 10 A (B)	65
Max. lamp no. on circuit break. 16 A (B)	76
Operating frequency	5060 Hz
Power factor λ	> 0.70
Claimed equiv. conventional lamp power	60 W


#### Photometrical data

Rated luminous flux	806 lm
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Luminous flux	806 lm
Color rendering index Ra	≥80
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	806 lm
Rated color temperature	2700 K
Color rendering index Ra	≥80

# Light technical data

Warm-up time (60 %)	< 1.00 s
Starting time	< 0.5 s

## Dimensions & weight



Overall length	110.0 mm

Diameter	60.0 mm
Outer bulb	A60
Length	110.0 mm

## Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	100 °C

## Lifespan

Nominal lamp life time	25000 h
Rated lamp life time	25000 h
Number of switching cycles	100000
Lumen maintenance at end of service life	0.70

## Additional product data

Base (standard designation)	E27	
Mercury-free	Yes	
Show WEEE picto	Yes	
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance)	
Mercury content	0.0 mg	

# Capabilities

Dimmable	Yes
----------	-----

## Certificates & standards

Energy efficiency class	A+
Energy consumption	9 kWh/1000h

#### Country-specific categorizations

Order reference	LEDSCLA60D 9W/8
-----------------	-----------------

## **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x	Gross weight	Volume
		height)		

4058075433861	Folding carton box 1	60 mm x 60 mm x 145 mm	48.00 g	0.52 dm³
4058075433878	Shipping carton box 10	322 mm x 134 mm x 120 mm	585.00 g	5.18 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **REFERENCES / LINKS**

For dimming conformity see

www.ledvance.com/dim

For further products and actual information concerning LED lamps see

www.ledvance.com/ledlamps

For Guarantee see

www.ledvance.com/guarantee

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.