PRODUCT DATASHEET LINEAR LED Slim RGBW 300

Linear LED Slim RGBW | High voltage undercabinet luminaires with RGBW technology

Areas of application

- Shelf and undercabinet lighting



Product benefits

- Direct connection to AC power supply thanks to integrated control gear
- Slim and sleek design
- Homogenous light distribution
- Easy and fast mounting on nearly every surface (adhesive tape or screws)

Product features

- Luminous flux: up to 350 lm
- Switch on and off, color changing and dimming via remote control
- Material: aluminum
- Color: silver
- Available in two lengths: 30 cm and 50 cm
- Connection of up to 10 luminaires (30 cm version) and up to 5 luminaires (50 cm version) possible



TECHNICAL DATA

Electrical data

Nominal wattage	4.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	50 mA
Power factor λ	> 0.5
Protection class	11
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	230 lm	
Luminous efficacy	58 lm/W	
Color temperature	3000 K	
Light color (designation)	Warm White	
Color rendering index Ra	≥80	
Standard deviation of color matching	≤6 sdcm	
Beam angle	110 °	

Dimensions & Weight

Length	300.00 mm
Width	49.00 mm
Height	18.00 mm
Product weight	315.00 g
Cable length	1500 mm



Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Aluminum Polycarbonate (PC)

Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C	
Temperature range at storage	-30+70 °C	
Type of connection	Plug type C (EU)	
Type of protection	IP20	
Dimmable	Yes	
Mounting type	Surface	
Mounting location	Cabinet undersides	
LED module replaceable	Not replaceable	

Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	100000

Certificates & Standards

CE / RoHS / EAC / REACH

EQUIPMENT / ACCESSORIES

- External cable (1.5 m) included

- Fixed connector and flexible connecting cable included

DOWNLOAD DATA

	DOWNLOAD DATA
POF	User instruction LINEAR LED SLIM RGBW
1	Tender documents Tender Text 4058075227651
PDF	Declarations of conformity LINEAR LED SLIM

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075227651	Folding box 1	41 mm x 71 mm x 400 mm	374.00 g	1.16 dm³
4058075227668	Shipping box 8	416 mm x 303 mm x 98 mm	3714.00 g	12.35 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.