

## PRODUCT DATASHEET VISION SENSOR

VISION SENSOR | Motion sensors with switching contact



---

### Areas of application

- Large areas
- Open-plan offices, corridors and storage rooms

---

### Product benefits

- Energy savings up to 35 % (compared to manual switching)

---

### Product features

- Motion sensor with switching contact
- Adjustable switch-off delay: 30 s to 20 min
- Maximum power consumption in stand-by mode: 0.25 W

---

## TECHNICAL DATA

### Electrical data

Nominal wattage	0.60 W
Nominal voltage	120...277 V
Mains frequency	50/60 Hz

### Dimensions & Weight

Length	115.60 mm
Width	115.60 mm
Height	40.00 mm
Diameter	116,0 mm
Product weight	135.00 g

### Colors & materials

Product color	White
---------------	-------

### Temperatures & operating conditions

Ambient temperature range	-10...+70 °C
---------------------------	--------------

### Capabilities

Dimmable	No
Maximum installation height	4,5 m
Detection area	21 m <sup>1)</sup>
Detection angle	140 ° <sup>2)</sup>
Load contact	5 A
Type of installation	On-top ceiling mounting

1) Maximum diameter

2) Approximately

### Certificates & Standards

Approval marks – approval	CE
Protection class	II
Type of protection	IP20

---

## EQUIPMENT / ACCESSORIES

- Suitable for up to 15 electronic control gears
  - Installation by means of Mounting Adapter possible
-

DOWNLOAD DATA


Documents and certificates		Document name
	Declarations of conformity	334824_Declaration of conformity – Mounting Adapter
	Declarations of conformity	EU Declaration of conformity HIGH BAY VISION SENSOR

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321957047	Folding box 1	115 mm x 64 mm x 115 mm	189.00 g	0.85 dm³
4008321956965	Shipping box 20	365 mm x 224 mm x 360 mm	4280.00 g	29.43 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.