


PRODUCT DATASHEET

Decor Perchero Wood

Decor Perchero | Decorative luminaires with hanger and light

Areas of application

- Bedrooms
- Entrance areas
- Offices



Product benefits

- Elegant design
- Soft light thanks to indirect light distribution

Product features

- Possibility to hang up the clothing
- Wall Luminaire
- 3000 K
- Housing material: metal



TECHNICAL DATA

Electrical data


Nominal wattage	6.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	36.000 mA
Inrush current time T _{h50}	1800 µs
Max. number of luminaires per miniature circuit breaker B16	29
Max. number of luminaires per miniature circuit breaker C16	49
Power factor λ	≥0.5
Total harmonic distortion	< 70 %
Protection class	II

Photometrical data

Luminous flux	80 lm
Total luminous flux of contained light sources	620 lm
Luminous efficacy	13 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	6 sdc _m
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Photobiological safety group acc. to EN62778	RG0

Dimensions & Weight

Length	800.00 mm
Width	50.00 mm
Height	200.00 mm
Product weight	900.00 g



DECOR PERCHERO WOOD

Materials & Colors

Product color	Black
Housing color	Black
Body material	Steel
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Application environment	Indoor
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	30000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)




Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	DECOR PERCHERO
	Declarations of conformity	DECOR PERCHERO
	Declarations of conformity UKCA	Fixed LUM

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075756786	Folding box 1	74 mm x 232 mm x 263 mm	987.00 g	4.52 dm³
4058075756793	Shipping box 4	315 mm x 253 mm x 288 mm	4346.00 g	22.95 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.