

PRODUCT DATASHEET Tracklight Middle Power Supply White

Tracklight accessories | Tracklight accessories



Areas of application

- Kitchens, living rooms, children's rooms or home offices
- Entrance areas

Product benefits

- Timeless elegant design
- High-quality materials

Product features

- Customisable modular tracklight system
- Accessories for tracklight system




TECHNICAL DATA

Electrical data

Nominal voltage	220240 V
Mains frequency	50/60 Hz
Protection class	1

Dimensions & Weight

Length	172 mm
Width	35.0 mm
Height	18.0 mm
Product weight	66.00 g



Materials & Colors

Р	roduct color	White
В	ody material	Plastic
		<u> </u>

Application & Mounting

Ambient temperature range	-20+40 °C
Type of protection	IP20

Certificates & Standards

Standards	RoHS / REACH / UKCA
Ball shot safe	No

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in

the event of a fault must be continuously connected to the protective earthing conductor.

- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

	Documents and certificates Document name	
PDF	User instruction / safety instructions	TRACKLIGHT MIDDLE POWER SUPPLY WT BK
PDF	Declarations of conformity	DL ESSENTIAL AND TRACKLIGHT
PDF	Declarations of conformity UKCA	DL ESSENTIAL AND TRACKLIGHT

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854386602	Folding box 1	22 mm x 48 mm x 180 mm	88.00 g	0.19 dm ³
4099854386619	Shipping box 6	105 mm x 76 mm x 190 mm	574.00 g	1.52 dm ³
4099854386626	Shipping box 60	400 mm x 226 mm x 215 mm	6141.00 g	19.44 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.