

# PRODUCT DATASHEET

## PANEL 1200 CABLE EXT TWIST LOCK

PANEL 1200 TWIST LOCK EXTENSION | Twist lock cable extension for Panel Comfort 1200



---

### Product benefits

- Improves visual appearance of the Panel in suspended application
- Extension cable on DC side allowing to hide the driver behind the ceiling
- Tool free installation by linking the extension wire into the existing twist lock connection between panel and driver

---

### Product features


- 2400 mm cable lengths
- Male or female twist lock connector on both ends
- Silver colored / transparent cable insulation for the most inconspicuous appearance possible
- Suitable for PANEL COMFORT 1200



## TECHNICAL DATA

### Dimensions & Weight

Diameter	13,0 mm
Length	2400 mm
Product weight	58.93 g



PL 1200 CABLE EXT TWIST LOCK

### Materials & Colors

Product color	Transparent
Body material	Polyvinylchlorid (PVC)

### Application & Mounting

Mounting location	Ceiling
-------------------	---------




### Certificates & Standards


Standards	CE / UKCA
-----------	-----------

## EQUIPMENT / ACCESSORIES

- Including 4 transparent cable holders to fix the cable at the metal wire of the Suspension Kit

## DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	PL CMFT 1200 P
	Legal information	Informationstext 18 Abs 4 ElektroG
	Declarations of conformity	CE Declaration of Conformity PL CABLE EXT TWIST LOCK


Documents and certificates		Document name
	Declarations of conformity UKCA	UKCA Declaration of Conformity PL CABLE EXT TWIST LOCK

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854018510	BAG 1	200 mm x 130 mm	64.00 g	
4099854026034	Shipping box 4	197 mm x 127 mm x 44 mm	314.00 g	1.10 dm <sup>3</sup>
4099854026041	Shipping box 24	277 mm x 217 mm x 159 mm	2243.00 g	9.56 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.