

# PRODUCT DATASHEET

## Decor Filament Table

Decor Filament | Luminaires with eye-catching floating filament design



### Areas of application

- Indoor applications

### Product benefits

- Individual control of brightness
- Easy operation by touch control
- Portable light weight product

### Product features

- Unique magnetic floating filament design
- Dimming function by touch control: 25%, 50%, 100%
- Integrated rechargeable lithium battery which can be charged via USB cable
- Practical handle for easy transportation (floor luminaire only)



TECHNICAL DATA

Electrical data

Nominal wattage	1.20 W
Nominal voltage	5 V
Nominal current	1000.000 mA
Max. number of luminaires per miniature circuit breaker C16	Not relevant
Protection class	III
Operating mode	Battery

Photometrical data

Luminous flux	100 lm
Total luminous flux of contained light sources	105 lm
Luminous efficacy	83 lm/W
Color temperature	2700 K
Light color (designation)	Warm white
Color rendering index Ra	> 80
Standard deviation of color matching	6 sdc <sub>m</sub>
Flickering metric (Pst LM)	<5
Stroboscope effect metric (SVM)	<0,4
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	280 °

Dimensions & Weight

Diameter	90.00 mm
Height	240.00 mm
Product weight	520.00 g
Cable length	1000 mm



DECOR FILAMENT TABLE

## Materials & Colors

Product color	Dark gray
Housing color	Dark gray
Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

## Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	USB
Type of protection	IP20
Dimmable	Yes
Type of dimming	3 DIM
Mounting type	Standing
Application environment	Indoor
Adjustable	No
With light source	Yes

## Lifespan

Lifespan L70/B50 at 25 °C	15000 h <sup>1)</sup>
Number of switching cycles	15000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## BATTERY

Battery size [GMS]	Others
Battery charging time	4 h

## Certificates & Standards

Standards	CE / UKCA
Replaceable light source (EPREL)	Not replaceable

## Additional product data

Number of illuminants	empty
-----------------------	-------



## EQUIPMENT / ACCESSORIES

- USB C cable

### Safety advice

- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.
- If the battery compartment (if applicable) does not close securely, stop using the product and keep it away from children. If you think batteries might have been swallowed or placed inside any part of the body, seek immediate medical attention.
- Please avoid: Maximal ambient temperature: +35 °C. Replacement of a battery with an incorrect type that can defeat safeguard (for example, in the case of some lithium battery types). Altitude during operation: 2000 m. Disposal of a battery into fire or a hot oven, or mechanically crushing or cutting of a battery, that can result in an explosion.

### DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	UI Decor Filament
	Declarations of conformity	CE Declaration Decor Filament Table and Floor

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075832916	Folding box 1	122 mm x 126 mm x 298 mm	674.00 g	4.58 dm <sup>3</sup>
4058075832923	Shipping box 6	384 mm x 270 mm x 325 mm	4660.00 g	33.70 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.