

PRODUCT DATASHEET

SMART+ MATTER Filament Globe 125 40

4.8W 827...865 Multicolor E27

SMART+ MATTER FILAMENT GLOBE MULTICOLOR | Globe shape with Matter technology



Areas of application

- General illumination through smart home technology
- Professional applications (hotels, bars, boutiques etc.) utilizing dynamic and robust ambient lighting effects
- When users want to mix and match smart home products from different manufacturers
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Wireless control via app or voice control
- Seamless integration with Matter-compatible systems
- Simplified set up process due to the standard user-friendly installation steps
- Enhanced security by implementing strong encryption and authentication protocols
- Lower energy consumption than incandescent or halogen lamps

Product features

- Controllable via SMART+ App (with minimum Android 8.0 or iOS 14.0) or any other Matter-compatible platforms
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Network protocol: Matter over WiFi
- Lifetime up to 15,000 h



- Compatible with Alexa, Google Home, Apple Home and other Matter-compatible platforms


TECHNICAL DATA

Electrical data

Nominal wattage	4.8 W
Construction wattage	4.80 W
Nominal voltage	220...240 V
Nominal current	50 mA
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz
Power factor λ	0.40
Claimed equiv. conventional lamp power	40 W
Operating mode	AC Mains

Photometrical data

Light color (designation)	RGBW
Lumen main.fact.at end of nom.life time	0.93
Standard deviation of color matching	≤ 9 sdc _m
Nominal luminous flux	470 lm
Luminous flux	470 lm
Luminous efficacy	97 lm/W
Adjustable color temperature	2700...6500 K
Color temperature	2700...6500 K
Color rendering index Ra	≥ 80
Flickering metric (Pst LM)	≤ 1
Stroboscope effect metric (SVM)	≤ 0.4



EPREL Data Spectral Diagram LEDr
AC42286 AC42287 AC42288
RGBTW

Light technical data

Beam angle	320 °
Starting time	< 0.5 s
Warm-up time (60 %)	< 0.50 s

Dimensions & Weight

Product weight	100.00 g
Diameter	124.00 mm
Maximum diameter	124 mm
Length	173.00 mm
Width	124.00 mm
Height	124.00 mm
Outer bulb [PICOS]	G124

Lifespan

Number of switching cycles	100000
Lifespan	15000 h
Lumen maintenance at end of service lifetime	0.93

Colors & materials

Product color	Clear
Body material	Glass

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Additional product data

Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Base (standard designation)	E27
-----------------------------	-----

Capabilities

Dimmable	Yes ¹⁾
----------	-------------------

¹⁾ Via App

Certificates & Standards

Energy efficiency class	F ¹⁾
Energy consumption	5.00 kWh/1000h
Standards	CE / UKCA
Type of protection	IP20

¹⁾ This product is exempt from the EU Energy Labelling Regulation (EU Directive 2019/2015)

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	Yes
Color-tuneable light source	Yes
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	RANGE
Networked standby power for CLS	<0.5 W
Claim of equivalent power	Yes
Chromaticity coordinate x	0.463-0.313
Chromaticity coordinate y	0.420-0.337
R9 Colour rendering index	>0
Beam angle correspondence	SPHERE_360
Survival factor	0.9
LED light source replaces a fluorescent light source	No

EPREL ID	1694304
Model number	AC52863,AC52863

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

Documents and certificates		Document name
	Extended installation guide	Insert WIFI MATTER StartUpG Lamps LDV
	Declarations of conformity	CE Declaration Smart Matter Filament
	Declarations of conformity UKCA	UKCA Declaration Smart Matter Filament
Photometric and lighting design files		Document name
	Spectral power distribution	EPREL Data Spectral Diagram LEDr AC42286 AC42287 AC42288 RGBTW

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854195020	Folding box 1	143 mm x 140 mm x 195 mm	188.00 g	3.90 dm ³
4099854195037	Shipping box 4	304 mm x 290 mm x 207 mm	1016.00 g	18.25 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.