

PRODUCT DATASHEET

URB LTRN V 59W ASYM PS 830-840 IP66 GY

URBAN LANTERN ASYMMETRIC | Fitting pathway, bicycle path lighting applications



Areas of application

- Replacement for luminaires with mercury vapor or metal halide lamps
- Streets
- Residential installations
- Pedestrian zones
- Parks
- Public areas

Product benefits

- Highly versatile due to selectable CCT and power steps (Power Select - PS)
- Low flicker light thanks to special electronic control gear
- Energy savings thanks to system efficacy of up to 139 lm/W
- Bright, robust and durable

Product features

- Protection class: II
- Lifetime (L80/B10): up to 100,000 h (at 25 °C)
- Type of protection: IP66
- Impact resistance: IK10
- Asymmetric light distribution

TECHNICAL DATA

Electrical data


Nominal wattage	59 W / 49 W / 42 W / 34 W ¹⁾
Nominal voltage	220...250 V
Mains frequency	50...60 Hz
Nominal current	150-190-215-260 mA
Inrush current	30.6 A
Inrush current time T _{h50}	300 µs
Max. number of luminaires per miniature circuit breaker B16	7
Max. number of luminaires per miniature circuit breaker C10	7
Max. number of luminaires per miniature circuit breaker C16	11
Power factor λ	> 0.90
Total harmonic distortion	< 20 %
Protection class	II
Surge capability (L-N)	6 kV
Operating mode	Integrated LED driver

¹⁾ For possible options refer to lumen/power table image

Photometrical data

Luminous flux	8200 lm / 6800 lm / 5840 lm / 4730 lm ¹⁾
Luminous efficacy	139 lm/W ¹⁾
Color temperature	3000 K / 4000 K
Light color (designation)	Warm White / Cool White
Color rendering index Ra	80
Standard deviation of color matching	5 sdcm
Low flicker	Yes
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	165° x 65°


¹⁾ For possible options refer to lumen/power table image



URB LTRN V29/59W ASYMPS

Dimensions & Weight

Diameter	395.00 mm
Height	417.00 mm
Product weight	4255.00 g
Cable length	250 mm



URBAN LANTERN

Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Aluminum
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	750 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-30...+50 °C
Temperature range at storage	-35...+80 °C

Type of connection	Cable, 3-pole
Type of protection	IP66
Protection class IK (shock resistance)	IK10
Dimmable	No
Mounting type	Post top
Mounting location	Pole
Application environment	Outdoor
Adjustable	No
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	100000 h ¹⁾
Lifespan L80/B10 at 25 °C	100000 h ¹⁾
Lifespan L80/B50 at 25 °C	100000 h
Lifespan L90/B10 at 25 °C	63000 h
Number of switching cycles	100000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	1490...1240...1060...850 mA
ECG - Output ripple current	< 20 %

Certificates & Standards

Standards	CE / UKCA / EAC / ENEC
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Added function	MULTI SELECT
----------------	--------------

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	URBAN LANTERN
	Legal information	Legal Insert URBAN LANTERN
	Legal information	URBAN LANTERN

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854246814	Shipping box 1	435 mm x 435 mm x 220 mm	4620.00 g	41.63 dm³

ADDITIONAL CATALOG INFORMATION

$\mathcal{W}_{\text{AG}}$	15	20	25	30	35	40	45	50
$\langle \mathcal{P}_{\text{AG}} \rangle$	0000	0000	0000	0000	0000	0000	0000	0000
invV	130	130	130	130	130	130	130	130
in	1800	1840	1880	1720	1670	1630	1670	1600

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.