

## PRODUCT DATASHEET

### Decor Gleam Table 2W Touch CCT DIM White

Decor Gleam | Decorative luminaires with translucent stones



#### Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Bedrooms

#### Product benefits

- High-quality look and feel
- High flexibility in the choice of the light source
- Sustainable solution thanks to exchangeable light sources
- Easy mounting

#### Product features

- Housing material: metal and terrazzo
- Highly versatile due to selectable CCT (only for table luminaire)
- Dimming function by touch control (only for table luminaire)
- Integrated rechargeable lithium battery which can be charged via USB cable (only for table luminaire)
- Textile cable (only for pendant luminaires)



TECHNICAL DATA

Electrical data


Nominal wattage	2.00 W
Nominal voltage	5 V
Protection class	III
Operating mode	Battery

Photometrical data

Luminous flux	40 lm
Total luminous flux of contained light sources	220 lm
Color temperature	2700 K / 3300 K / 4500 K
Reference control setting of contained light source (Kelvin)	2700 K
Light color (designation)	Warm White / Brilliant white / Cool White
Color rendering index Ra	80
Standard deviation of color matching	< 9 sdc <sub>m</sub>
Photobiological safety group acc. to EN62778	RG0

Dimensions & Weight

Length	100.00 mm
Width	100.00 mm
Height	97.00 mm
Product weight	720.00 g
Cable length	1000 mm



DECOR GLEAM TABLE 2W  
TOUCH CCT DIM

Materials & Colors

Product color	Beige
Housing color	Beige
Body material	Terrazzo

Glow Wire Test according to IEC 60695-2-12	650 °C
--	--------

### Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	USB
Type of protection	IP20
Dimmable	Yes
Type of dimming	Push DIM
Mounting type	Standing
Mounting location	Table
Adjustable	No
With light source	Yes

### Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	15000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### BATTERY

Type of Battery	Lithium ion
Battery size [GMS]	Others
Battery charging time	6 h

### Certificates & Standards

Standards	CE / UKCA
Replaceable light source (EPREL)	Not replaceable


### Additional product data

Product remark	Available from June 2025
----------------	--------------------------

### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- Please avoid: Maximal ambient temperature: +35 °C. Replacement of a battery with an incorrect type that can defeat safeguard (for example, in the case of some lithium battery types). Altitude during operation: 2000 m. Disposal of a battery into fire or a hot oven, or mechanically crushing or cutting of a battery, that can result in an explosion.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	DECOR GLEAM TABLE TOUCH-CCT-DIM

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075846821	Folding box 1	132 mm x 132 mm x 132 mm	798.00 g	2.30 dm <sup>3</sup>
4099854475467	Shipping box 4	290 mm x 290 mm x 155 mm	3537.00 g	13.04 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.