

PRODUCT DATASHEET

Decor Flip Mobile Table 3.5.W Touch DIM Blue

Decor Flip | Decorative luminaires made of felt



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Bedrooms

Product benefits

- Design delights your home with a warm atmosphere
- Eye-catching luminaire made of felt
- Lampshade color, size or direction selectable
- High flexibility in the choice of the light source
- Sustainable solution thanks to exchangeable light sources
- Easy mounting

Product features

- Housing material: felt
- Dimming function by touch control (only for table luminaire)
- Integrated rechargeable lithium battery which can be charged via USB cable (only for table luminaire)
- Textile cable



TECHNICAL DATA

Electrical data


| | |
|------------------|---------|
| Nominal wattage | 3.50 W |
| Nominal voltage | 5 V |
| Protection class | III |
| Operating mode | Battery |

Photometrical data

| | |
|--|------------|
| Luminous flux | 70 lm |
| Total luminous flux of contained light sources | 240 lm |
| Luminous efficacy | 20 lm/W |
| Color temperature | 3000 K |
| Light color (designation) | Warm White |
| Color rendering index Ra | 80 |
| Photobiological safety group acc. to EN62778 | RG0 |

Dimensions & Weight

| | |
|----------------|-----------|
| Diameter | 235.00 mm |
| Height | 255.00 mm |
| Product weight | 550.00 g |



DECOR FLIP MOBILE TABLE
2WTOUCH DIM

Materials & Colors

| | |
|--|--------|
| Product color | Blue |
| Housing color | Blue |
| Body material | Felt |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |

| | |
|-----------------|--------|
| Mercury content | 0.0 mg |
|-----------------|--------|

Application & Mounting

| | |
|------------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
| Temperature range at storage | -20...+80 °C |
| Type of connection | USB |
| Type of protection | IP20 |
| Dimmable | Yes |
| Type of dimming | Push DIM |
| Mounting type | Standing |
| Mounting location | Table |
| Adjustable | No |
| With light source | Yes |

Lifespan

| | |
|---------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C | 30000 h ¹⁾ |
|---------------------------|-----------------------|

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

BATTERY

| | |
|--------------------|--------|
| Battery size [GMS] | Others |
|--------------------|--------|

Certificates & Standards

| | |
|----------------------------------|-----------------|
| Standards | CE / UKCA |
| Replaceable light source (EPREL) | Not replaceable |




Additional product data

| | |
|-----------------------|---|
| Product remark | Maximum bulb wattage: 10 W (3.5 W LED) / Available from June 2025 |
| Number of illuminants | 1 |

Safety advice

- The external flexible cable or cord of this luminaire cannot be replaced; if the cord is damaged, the luminaire shall be destroyed.
- Please avoid: Maximal ambient temperature: +35 °C. Replacement of a battery with an incorrect type that can defeat safeguard (for example, in the case of some lithium battery types). Altitude during operation: 2000 m. Disposal of a battery into fire or a hot oven, or mechanically crushing or cutting of a battery, that can result in an explosion.

DOWNLOAD DATA

| Documents and certificates | | Document name |
|--|--|------------------------------------|
|  | User instruction / safety instructions | DECOR FLIP MOBILE TABLE TOUCH-DIM |
|  | Declarations of conformity | CE Declaration Flip Mobile Table |
|  | Declarations of conformity UKCA | UKCA Declaration Flip Mobile table |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------|
| 4058075848566 | Folding box 1 | 192 mm x 192 mm x 293 mm | 868.00 g | 10.80 dm³ |
| 4058075848573 | Shipping box 4 | 400 mm x 400 mm x 318 mm | 4416.00 g | 50.88 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.