

# PRODUCT DATASHEET DALI Sensor Coupler E

# DALI Sensor Coupler E | DALI sensor coupler for external sensors



#### Areas of application

- Connection of light and presence sensors in DALI systems
- Ceiling or independent installation via ECO CI KIT possible
- Suitable for external light and presence sensors
- Installation in industry and office luminaires
- Corridors
- Warehouses

## Product benefits

- Small housing design

#### **Product features**


- Suitable for daylight-dependent control

#### TECHNICAL DATA

#### Electrical data

Nominal wattage	0.30 W
Nominal voltage	230 V
Mains frequency	50 Hz

## **Dimensions & Weight**



Length	118.00 mm
Mounting hole spacing, length	110,0 mm
Width	30.00 mm
Height	21.00 mm
Product weight	50.00 g

#### Temperatures & operating conditions

Ambient temperature range -20+50 °C
-------------------------------------

## Additional product data

|--|

## Capabilities

Dimmable	No
Dimming interface	DALI
Number of control outputs	1
Type of installation	Luminaire integration/Ceiling integration

### **Certificates & Standards**

Approval marks – approval	CE
Protection class	II
Type of protection	IP20

### EQUIPMENT / ACCESSORIES

- Separate installation possible with ECO CI KIT

#### DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	612042_Technical Instruction DALI Sensor Coupler E
PDF	User instruction / safety instructions	DALI Sensor Coupler E
PDF	Declarations of conformity	EC-DoC LMS Sensor Coupler and Sensor 9C1-3402820-EN-02 2019

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4052899230491	Folding box 1	128 mm x 37 mm x 27 mm	64.00 g	0.13 dm <sup>3</sup>
4052899230507	Shipping box 25	200 mm x 140 mm x 147 mm	1746.00 g	4.12 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.