

# PRODUCT DATASHEET

## ENDURA Garden 3 Dots Extension 3000K

ENDURA GARDEN DOT | Decorative light dots for outdoor use

---

### Areas of application

- Gardens, balconies and other outdoor areas



---

### Product benefits

- Easy and quick installation

---

### Product features

- Protection class (dots): IP65
- Protection class (power supply): IP44
- Extension up to maximum 18 dots
- Color temperature: 3,000 K (Warm White)



Nominal wattage	2.10 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor $\lambda$	> 0.5
Protection class	III
Operating mode	Mains voltage

Luminous flux	160 lm
Total luminous flux of contained light sources	210 lm
Luminous efficacy	52 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥80
Standard deviation of color matching	≤6 sdcn
Beam angle	33.00 °

Diameter	23.00 mm
Width	23.00 mm
Height	96.00 mm
Product weight	80.00 g

Page 2 of 4

Body material	Polycarbonate (PC)
Cover material	Polycarbonate (PC)

### Application & Mounting

Ambient temperature range	-20...+40 °C
Type of connection	Plug type C (EU)
Type of protection	IP65
Dimmable	No
Mounting type	Ground spike
Mounting location	Ground
Application environment	Outdoor
With light source	Yes

### Lifespan

Lifespan L70/B50 at 25 °C	25000 h <sup>1)</sup>
Number of switching cycles	12500

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Certificates & Standards

Standards	CE / EAC
Replaceable light source (EPREL)	Not replaceable


### EQUIPMENT / ACCESSORIES


- Power supply included only in basic set
- Complete mounting and connecting accessories included

### Safety advice

- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.

### DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	ENDURA GARDEN DOT

Documents and certificates		Document name
	Declarations of conformity	ENDURA GARDEN DOT EXT3P 2,1W TP LEDV

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075478510	Folding box 1	102 mm x 44 mm x 109 mm	100.00 g	0.49 dm <sup>3</sup>
4058075478527	Shipping box 4	180 mm x 125 mm x 120 mm	534.00 g	2.70 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.